RESERVED AT THE BIM CONSTRUCTION SITE

Kristoffer Bugge, Artemis Valanis, Øyvind Engelstad (Norconsult)

FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

Organised by



Platinum Partners





Diamond Partner



What is BIM without surveying engineers?





Surveying engineers should take a new step





In order to build we need a solid foundation





The contribution of a surveyor on BIM projects

- establishment of a good starting point for all projects
- accurate documentation of space and structures
- optimized work processes
- seamless integration between field and office for
 - improved collaboration
 - better time and risk management
 - avoid waste of time and resources
 - avoid mistakes and unnecessary costs



BIM in Norconsult

- Overall BIM Strategy
- BIM as tool for engineering
- BIM at the construction site
- BIM as basis for FM
- Benefits of employing BIM





Overall BIM strategy in Norconsult

- Norconsult shall employ **BIM on all projects**
- Investment on both BIM Tech and BIM Team
- Development of standardized work processes, which are documented in the company BIM manuals
- Separate models for every discipline during processing
- Combination of models from all disciplines in the collaboration environment
- Interdisciplinary control inside collaboration environment
- All BIM models include built-in information about quantities and can be used in all stages of a project



Project descrition:

- New hydropower plant
- The biggest of its kind
- Entirely designed in 3D as a BIM model
- A Completely Paperless Project
- 1 sq Km Project Area
- Aerial and terrastrial Laser Scanning, Aerial and Ground image data, GIS data, Geodetic, geological and seismic surveys all employed for the initial documentation.



New Concept Design





New Concept Design





Bringing BIM into the construction site

- Establishment of a geodetic network
- Capture and modelling of terrain
- Scanning and modelling of existing structures and infrastructure
- Development, evaluation and optimization of concept in BIM
- Continous monitoring of construction progress
- Update the «as built» model
- Continuous control of costs and quantities(5D BIM)























Field and design integration





Design and construction integration





Field and Construction integration





Interdisciplinary collaboration





Integration between Model and "Bills of quantities"





Integration of Information





Integration of Information

Selection Tree 🖉 🗙		Properties	(¥)
Standard 👻		Revit Material Au	todesk Material Element ID Element SI + +
G_Vamma12_Tipp_For Orientering.nwc		Proset	Volum
A_Vamma12_Arkitekt_For Orientering.nwc		Fingency	Paker Par
Punktsky 01.rcs		Family	Nebar Bar
Punktsky 02.rcs		Category	Structural nebar
B S Vamma12_Konstruksjon_For Orientering.nwc		IO IAI elucat	5692/1/
Gal G 2015-10-19_Krattstasjonsområdet Graveplan.nwc		SORSTK A	6755 mm
B G 2015-09-11 Innorenssoner nur		Bar Length	6754 mm
BR Vamma12 Mekanisk For Orientering.nwd		R	49985 mm
⊕ M_A01_5143332_Vamma12.iam		Standard Bend D	32 mm
- Commentation		Style	0
⊕ G_Eksisterende terreng_totalt_Koter_0,5m_UTM_For_Orientering.dwg		Workset	Rebar
⊕ G_Vann_ytre_UTM_For_Orientering.dxf		Shape	RebarShape "67 0 0", #186107
⊕ G_Vann_indre_UTM_For_Orientering.dxf		Type	RebarBarType "ø12", #182753
B B Eksisterende konstruksjoner og veier_UTM_For_Orientering.nwc		SOFISTIK_E	0 mm
B 2015-11-04_Inntak_Grave og sprengningsplan inntak og tangdam.nwc		SOFISTIK_Distan	. 0 mm
		h	0 mm
- @% Generic Models		Schedule Mark	10
- B% Lines		Bend Diameter	32 mm
-⊕\$\$ Structural Foundations		Reinforcement V	15279,45 cm ²
Structural Rebar		Quantity	20
- Container		a	6754 mm
🔍 Rebar Bar		Layout Rule	2
		SOFISTIK_Bar_L	6755 mm
- Contraction		Revision	1
- Tel Rebar Bar		Phase Lreated	Phase "New Construction", #0
- Bar Bar		SURIS IIILE	46360 mm
🕀 🌐 Rebar Bar		Sancing	150 mm
- 🕀 📾 Rebar Bar		Total Bar Leogth	135100 mm
- @@ Rebar Bar		SOFISTIK C	0 mm
🕀 📾 Rebar Bar		SOFISTIK Mark	20
10 m Rebar Bar		Sum Delmål	6754 mm
- H G Pahar Bar		Rebar Revision	H01
The Rehar Bar		Shapecode	67
🕀 📾 Rebar Bar		b	0 mm
- 🕀 🌐 Rebar Bar		SOFISTIK_Runni	0
- 🕀 🌐 Rebar Bar		Bar Diameter	12 mm
🕀 🗐 Rebar Bar		SOFISTIK_Shape.	. 67
- ⊕ ∰ Rebar Bar		Partition	FD1
- Helar Bar		e	0mm
- (i)		Family and Type	Hebarbar type @12 , #182/53
🕀 🕼 Rebar Bar		Estimated Reinfor	15370 4E 1
🖽 📾 Rebar Bar		SOESTK D	Down
-: :: :: :: :: :: :: :: :: :: :: :: :: :		F	0mm
-: :: :: :: :: :: :: :: :: :: :: :: :: :		Host Category	6
		Edited by	lahas
		C	0 mm
		Mark	FD1
		SOFISTIK_F	0 mm
		SOFISTIK_Distan	. 0 mm
		d	0 mm
	SY(1 AV C 169) - P LST III - TAMAN SUM (-2)	Type Id	ReharBarTyne "ø12" #182753
		1	· · · · · · · · · · · · · · · · · · ·



From Design to construction







From Design to construction





Monitoring of Construction progress







Monitoring of Construction progress





Update to As-Built status





BIM in Norconsult





PROCESS REVIEW AND FEEDBACK



Quality Checked Data





Quality Checked Data





Conclusions



BIM to Construction site benefits

- Paperless construction
- Surveying based on the BIM model
- Navigation in the BIM model on portable devices
- Connection between objects in BIM model and codes on the bill of quantities
- Connection between elements of BIM model and available documentation
- Prefabrication of re-einforcement and various elements based on the BIM model
- Direct quality check by import of field data into collaboration model
- «As built» information integrated into the BIM model
- Control of quantities and costs based on BIM
- Scheduling and audits in BIM

• • • •



And a bit of BIM fun





We certainly feel inspired! How about you?







Thank you